



The
Patent
Office

PCT/9300/00749



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 04 MAY 2000	
WIPO	PCT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

(4)


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

BEST AVAILABLE COPY



Signed

AmBrewer


Dated

12 April 2000

is Page Blank (usp

Patents Act 1977

(Rule 16)



08MAR99 E430714-1 C00446
P01/7700 0.00 - 9905173.2

Request for Grant of a Patent

The Patent Office
Cardiff Road
NEWPORT NP9 1RH

1.	Your reference	P79608		
<hr/>				
2.	Patent Application number <i>(the Patent Office will fill in this part)</i>	9905173.2		- 5 MAR 1999
<hr/>				
3.	Full name, address and postcode of the or of each Applicant <i>(underline all surnames)</i>	SLS Biophile Limited Units 1 & 2, Heol Rhosyn, Dafen Industrial Estate, Llanelli, Carmarthenshire SA14 8LX United Kingdom		
	Patent Office ADP Number <i>(if you know it)</i>			
	If the applicant is a corporate body, give the country/state of its incorporation	United Kingdom 7165889001		
<hr/>				
4.	Title of the Invention	Wrinkle Reduction		
<hr/>				
5.	Name of your Agent <i>(if you have one)</i>	URQUHART-DYKES & LORD		
	"Address for Service" in the United Kingdom to which all correspondence should be sent <i>(including the postcode)</i>	Alexandra House 1 Alexandra Road SWANSEA SA1 5ED United Kingdom		
	Patents ADP Number <i>(if you know it)</i>	1644005		
<hr/>				
6.	If you are declaring priority from one or more earlier Patent Applications, give the country and the date of filing of the or of each of these earlier Applications and <i>(if you know it)</i> the or each	Country	Priority application No. <i>(if you know it)</i>	Date of Filing <i>(Day/month/year)</i>
<hr/>				
7.	If this Application is divided or otherwise derived from an earlier UK Application, give the Number and the Filing Date of the earlier Application	Number of earlier application	Date of Filing <i>(Day/month/year)</i>	
<hr/>				
8.	Is a Statement of Inventorship and of Right to Grant of a Patent required in support of this request ? <i>(Answer 'Yes' if:</i>		YES	
	a) any Applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an Applicant, or c) any named Applicant is a corporate body.)			

9. Enter the number of sheets for any of the following items you are filing with this Form. Do not count copies of the same document

Continuation sheet of this Form	0
Description	14 / 25
Claim(s)	5
Abstract	1
Drawing(s)	3 + 3

10. If you are also filing any of the following state how many against each item

Priority documents	0
Translations of priority documents	0
Statement of Inventorship and Right to Grant a Patent (<i>Patents Form 7/77</i>)	0
Request for Preliminary Examination (<i>Patents Form 9/77</i>)	0
Request for Substantive Examination (<i>Patents Form 10/77</i>)	0
Any other documents (<i>please specify</i>)	0

11. I/We request the grant of a Patent on the basis of this Application

Signature

Date

URQUHART-DYKES & LORD

4th March 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr. G.M. Davies - 01792 474327

Warning

After an Application for a Patent has been filed, the Comptroller of the Patent Office will consider whether Publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a Patent abroad without first getting written from the Patent Office unless an Application has been filed at least 6 weeks beforehand in the United Kingdom for a Patent for the same invention and either no direction prohibiting Publication or communication has been given, or any such direction has been revoked.

Wrinkle Reduction

5 The present invention relates to a method of reducing wrinkles from a superficial area of mammalian skin tissue, and apparatus therefor.

10 The application of laser technology in healthcare is well known, and the use of lasers in medical applications has been studied extensively since the early 1960's. In recent years an increasing interest has been shown in cosmetic applications. Two such cosmetic applications are skin resurfacing and wrinkle removal; in this field lasers
15 can be used as an alternative to surgical facelifts.

20 There is a distinct difference between wrinkle removal and skin resurfacing. Skin resurfacing is where laser energy vaporizes thin layers of the epidermis without breaking through the basal layer into the dermis. This is essentially a superficial process primarily used to give the skin a "fresher" appearance. However, wrinkle removal as a more aggressive technique where tissue is removed layer by layer, invading the dermis and effectively
25 inducing a second degree burn. Heat is deposited in the dermis shrinking the collagen and tightening the skin.

30 In young skin, the collagen just beneath the surface of the skin forms an organized lattice with good elasticity and flexibility. During aging, the collagen changes its structure impacting negatively on the cosmetic appearance.

of the skin. Several techniques have been developed to induce a "controlled injury" to the dermis in an attempt to generate rejuvenation of the collagen structure returning the skin to an earlier cosmetic appearance. During the 1990's a laser approach to wrinkle removal has been introduced.

For known wrinkle removal techniques, the wavelength is chosen so that the laser energy is highly absorbed in water, the current lasers of choice being the CO₂ laser at 10.6 μ m wavelength and the Erbium YAG laser at 2.94 μ m wavelength. In this non-selective process, pulses of laser energy are applied to the skin surface, each pulse vaporizing a layer of tissue between 30 μ m to 60 μ m in thickness. Normally, the first pass of the laser removes a thin layer of the epidermis without damaging the basal layer. Successive passes over the same area penetrate into the dermis and heat the collagen. The laser operator sees this thermal build-up "shrink" the skin in "real time", tightening up the skin's appearance. When the desired clinical outcome is achieved, the operator ceases applying laser pulses. It is therefore apparent that the quality of the cosmetic result is highly dependent upon the experience and skill of the operator.

In the case of CO₂ laser wrinkle removal, post-treatment supervision of the patient is a necessity. Immediately after treatment, the skin is essentially an open wound requiring dressings in place for 2-10 days. Additionally, topically applied lotions are required for patient comfort and prevention of infection. Post-operative infection is

common, primarily due to removal of the natural protective barrier of the skin, with a reported incidence of between 4.5 to 7%.

5 On average, with CO₂ laser wrinkle removal, post-treatment
erythema is present for 4-5 months. This compares to 2-3
months following a Chemical Peel. Also, the incidence of
side effects is significant, the most common being
hyperpigmentation occurring in 30-40% of cases. Higher
10 incidences are reported in darker skin types. A delayed
hypopigmentation, which can occur up to a year after the
procedure was performed, has recently emerged as a
complication of aggressive laser resurfacing. Many of the
eminent laser resurfacing surgeons have resorted to less
15 aggressive techniques.

The effect of known procedures is two fold:

(a) the laser induces denaturing of the collagen in the
20 dermis, and the formation of cross links, which
results in a tightening effect stretching the skin,
reducing or removing the wrinkles (it is thought that
the thermal threshold for this effect is a
temperature of 70°C); and

25

(b) the changes to the dermis induce the generation of
new collagen which develops using the matrix created
by the denatured collagen as a foundation.

30 The skin-resurfacing and wrinkle removal procedure
outlined above is considered by many experts in the field

as a significant improvement over previously used surgical methods. The procedure uses the laser's ability to deliver high energy density at the surface of tissue and hence ablate the surface tissue in a well controlled manner. Continuing to remove the tissue, layer by layer is designed to damage the collagen and hence induce wrinkle removal. This second stage of the procedure is primitive; the skin weeps, scabs form and redness of the skin appears for many weeks.

It is therefore the primary object of the present invention to provide a technique for removing wrinkles from a superficial area of mammalian skin tissue without causing secondary burns and other problems associated with traditional wrinkle removal.

The present invention provides a method of removing wrinkles from a superficial area of mammalian skin tissue. The dermal layer of the tissue is irradiated through the basal layer by radiation selected to be absorbed by a chromophore in the dermal layer such that collagen present in the dermal layer is heated, while the basal layer remains intact so as to substantially inhibit contact of the dermal layer with ambient air.

According to a further aspect, the invention provides apparatus for cosmetic reduction of wrinkles on a superficial area of mammalian skin, the apparatus comprising a radiation delivery system for delivering a radiation beam of predetermined monochromatic wavelength or narrow wavelength bandwidth to the skin, the radiation

delivery system including a pulsation system for pulsing the radiation delivered according to a predetermined regime, and an optical arrangement for focussing the beam such that the total radiation energy density delivered to the skin is substantially in the range $0.5\text{J}/\text{cm}^2$ to $5\text{J}/\text{cm}^2$ per pulse.

The irradiation of the dermal layer in the method according to the invention is tailored to shrink the skin tissue without damage to the dermis (in other words, without causing second degree burns) because the barrier provided by the basal layer remains intact. This is achieved by selecting the required radiation wavelength to match the characteristic absorption wavelength of the chromophore whilst being absorbed to an insignificant degree in the epidermis and basal layer. The energy delivered per pulse is also tailored to ensure that ablation does not occur of the target structure, but rather that energy absorbed in the target provides sufficient heating that heat energy diffusing outwards from the target heats the surrounding tissues to a degree sufficient to thermally induce shrinkage of the surrounding tissue and also stimulate the production of new tissue components such as elastin and collagen.

If the target for the laser has an appropriate chromophore (a substance that absorbs a specific wavelength and transmits or scatters at other wavelengths) then the laser can be used to modify that target selectively within an inhomogeneous volume of tissue. Occasionally, the desired target does not have a suitable chromophore of its own but

exists in close proximity to another material which has such a chromophore which can be selectively targeted. Such interaction is called secondary selective interaction.

5

10

An artificial chromophore may be introduced into the desired area for wrinkle reduction, or a naturally occurring chromophore may be selected. In a preferred embodiment of the technique, the naturally occurring chromophore selected is oxyhemoglobin of the dermal plexus which has wavelength absorbtion peaks at 585nm and 815nm, at which wavelengths absorbtion in surrounding tissue components is relatively low.

15

20

25

According to a further aspect, the invention therefore provides apparatus for cosmetic reduction of wrinkles on a superficial area of mammalian skin, the apparatus comprising a radiation delivery system for delivering substantially monochromatic radiation in a bandwidth of substantially 15 nm or less in at least one of the ranges 570nm to 600nm and 750nm to 850nm, the delivery system including a pulsation system for pulsing the radiation delivered according to a predetermined regime in which the energy density of the substantially monochromatic radiation in the bandwidth of substantially 15nm or less delivered to the skin is substantially in the range 0.5J/cm² to 5J/cm² per pulse.

30

The method according to the invention is non-invasive and non-ablative and can readily be performed by non-medical personnel. The total energy delivered per pulse is

sufficient to effect the required physical change in the tissue surrounding the target chromophore without causing ablation of the target or other skin components through which the radiation passes.

5

The radiation is preferably substantially monochromatic or at least of a relatively narrow wavelength bandwidth to ensure that it is preferentially selectively absorbed by the target chromophore. A laser source may be used to produce the required wavelength, or a light source, such as an LED may be used with appropriate filtering to permit the selected wavelength (or narrow wavelength band) to pass.

10

15

The irradiation may be by means of a source of visible or infra-red radiation (suitably filtered to remove deleterious ultra-violet radiation if necessary). The radiation may be coherent (that is from a laser source). Such a laser source may be, for example, a dye laser, a ruby laser, or a semiconductor laser. If a dye laser is used, its wavelength is preferably such that it is absorbed by oxyhemoglobin (as naturally occurring chromophore present in blood vessels in the dermis). Alternatively, the superficial area may be treated with an artificial chromophore which is absorbed into the dermal

20

25

layer. Such an artificial chromophore may be applied to the epidermal layer in the form of a liposome-containing topical formulation. The chromophore may then permeate through the basal layer for delivery to the dermal layer.

30

When a laser is used, it may be arranged to scan the

superficial area and/or to irradiate the dermal layer in pulses. When the laser is in pulsed mode, the pulses typically have duration of $10\mu\text{sec}$ to 10msec (more preferably $200\mu\text{sec}$ to 1msec).

5

It is sometimes desirable to remove part of the epidermis prior to irradiating the dermal layer according to the invention. Such epidermis removal (known as skin resurfacing) may be effected mechanically (for example by abrasion), or by means of laser radiation. When laser radiation is used for this purpose, it is typically a scanner controlled CO_2 laser source.

10

The energy density per pulse is preferably accurately controlled to ensure that a maximum threshold level (substantially of $5\text{J}/\text{cm}^2$) is not exceeded.

15

The invention will now be further described in specific embodiments, by way of example only and with reference to the accompanying drawings, in which:

20

Figure 1 is a schematic representation of the three outermost layers of mammalian skin tissue;

25

Figure 2 is a schematic representation of partial removal of the epidermis (skin resurfacing), which is an optional step according to the invention;

30

Figure 3 is a schematic illustration of the result of a prior art method of wrinkle removal, which is surgical because it involves full removal of the

epidermis in a selected area and therefore exposure of the dermis and consequent second degree burning;

5 Figure 4 is a schematic illustration of the result of the method according to the invention, showing that the epidermis is partially intact and the basal layer fully intact;

10 Figure 5, is a schematic diagram of a first embodiment of wrinkle reduction apparatus according to the invention;

15 Figure 6 is a schematic diagram of an alternate embodiment of wrinkle reduction apparatus according to the invention;

20 Figure 7 is a schematic representation of an optical delivery system forming part of apparatus according to the invention; and,

Figure 8 is a graphical representation showing the intensity profile of the radiation delivered using apparatus according to the invention.

25 Referring to Figure 1, the basic skin structure of mammalian skin tissue comprises three layers, the outermost epidermis 1 which is adjacent to the basal layer 2 and then the dermis 3.

30 Referring to Figure 2, partial removal of an area 4 of epidermis 1 by means of CO₂ laser radiation is known as

skin resurfacing. This stage represents the first step of a prior art method but is an optional step according to the invention. Both the basal layer 2 and the dermis 3 are unaffected by the laser radiation.

5

As shown in Figure 3, prior art method of wrinkle removal results in complete removal of an area 5 of epidermis 1 and basal layer 2 by repeated exposure to CO₂ laser radiation. Partial removal of the dermis 3 also occurs, as represented by 6, leaving the dermis exposed to air. This causes a second degree burn which is slow to heal and a risk of infection.

10

As shown in Figure 4, the method of wrinkle removal according to the invention results in partial removal of the epidermis 1 (this is an optional step as described in Figure 2 above) and the basal layer 2 is left intact, such that the dermis 3 is not exposed to air. Laser radiation 7 is applied to the tissue and selectively absorbed by a chromophore in the dermis 3, heating the collagen and shrinking the skin hence removing the appearance of wrinkles.

20

In a preferred embodiment, the target chromophore selected is oxyhemoglobin in the dermis 3 which has absorption peaks at approximately 585nm and 815nm. The apparatus shown in Figure 5 comprises a laser radiation delivery system 101 comprising a flashlamp excited pumped dye laser including a laser head 102, dye reservoir 103 and pump 104. A flowmeter 105 regulates dye flow to the laser cavity in the laser head 102 and a cooling system 106

25

30

cools the laser head 102 and dye reservoir 103. The system is controlled by a microprocessor controller 107 which operates voltage control of a pulse forming network 108 (including a capacitor and inductor network) which initiates a discharge pulse and consequently a pulsed beam laser output from laser head 102. Voltage control and feedback is provided between the microprocessor controller 107 and pulse forming network 108 via link 109. Temperature monitoring feedback is provided between the cooling system and the controller 107 via link 110.

The laser head operates to output controlled pulses of laser radiation having wavelength in the range 577nm to 585nm and a pulse duration in the range 200 μ s to 1ms. To produce the required wavelength an appropriate laser dye is selected (such as Rhodamine 575 or Pyromethene 590), the concentration of the dye solution is controlled.

Control of the pulse duration for the dye laser arrangement 101 is achieved by accurate control of the energy delivered to the exciting flashlamps in the laser head 102 by tailoring the capacitor and inductor values in the pulse forming network 108.

The energy is delivered to the skin surface via a fiberoptic tube 112 (see Figure 7) and a focussing optical lens arrangement 113 which is configured to focus a light spot onto the skin tissue surface so as to have a spot diameter within the range 1mm to 10mm, and an intensity distribution across the spot diameter that is substantially uniform (i.e. "a top hat" distribution), as

shown in Figure 8. Providing optics to ensure that the uniform energy distribution results in even heating of the tissue without the occurrence of "hot spots" which could result in tissue damage/ablation.

5

The radiation parameters are also selected to ensure that the total radiation energy density delivered per pulse falls within the range $0.5\text{J}/\text{cm}^2$ to $5\text{J}/\text{cm}^2$. It is particularly important that the selected upper threshold value ($5\text{J}/\text{cm}^2$) is not exceeded significantly as delivery of a higher energy densities of radiation per pulse can result in unwanted effects on the skin (such as ablation and/or other damage).

10

For the dye laser system 101 of Figure 1, the energy density of the radiation delivered to the skin is controlled by adjustment of the flashlamp output energy (which in turn controls the laser output energy). The laser output energy in conjunction with the spot site determines the energy density delivered. Accurate control is achieved by control of the dye circulation rate, the dye temperature and the flashlamp output energy. Dye circulation rate is important because repeated pulsing of the same volume of dye, without circulation, reduces the output energy of the laser head 102. Increasing or

20

25

30

decreasing the dye temperature has an affect on the energy output of the laser head 102. The flashlamp output energy is controlled by varying the voltage with which the capacitors in the pulse forming network 108 are charged; feedback of the capacitor voltage via link 109 is therefore important.

The energy density required will vary within the specified range from person to person, depending upon skin colour.

5 Referring to Figure 6, there is shown an alternative embodiment of apparatus for performance of the invention in which an LED or semiconductor laser device 202 may be utilised to produce the output radiation 220. A user interface 213 enables input into a microprocessor controller 207 which is used to control a power supply unit 214 to ensure that the required current is supplied to the LED or semiconductor laser device 220. A temperature sensor 215 provides temperature feedback via a link 210. Output 216 from controller 207 sets the current supplied by the power supply unit 214 to the device 202; input 217 into the controller 207 provides current monitoring feedback. Control of the pulse duration is achieved by pulsing the current supply from power supply unit 214 to the LED or semiconductor laser device 202.

20 High intensity LED devices are capable of producing wavelengths corresponding to the 585nm absorption peak of oxyhaemoglobin. The optical system (including lens 113) may include filters arranged to narrow the band of radiation passing from the LED to the target area of the skin. Where lasers are used, the output may be monochromatic. Alternatively, or in the case where LED's are used, the radiation delivered may be "effectively" monochromatic, or of a relatively narrow band width (typically within a band width of 15nm or less).

25

30

Where a semiconductor laser device is used, the output may correspond to the second (higher) absorption peak (815nm) for oxyhaemoglobin.

5 Whilst the invention has been described in relation to
delivery of effectively monochromatic radiation (or within
specific narrow band widths) at one or other of the
oxyhaemoglobin absorption peaks of 585nm and 815nm, it is
clear that the beneficial effect of the invention can be
10 achieved to a certain degree by using wavelengths
relatively close to, but either side, of the respective
absorption peaks. Preferred wavelength ranges for
operation are 570nm to 600nm and 750nm to 850nm for
targeting oxyhaemoglobin.

15 Where an artificial chromophore is used, the wavelength
(or narrow band of wavelengths) is selected to correspond
to a characteristic absorption wavelength of the relevant
chromophore. It remains important to ensure that the
20 total energy delivered per pulse is below the threshold
damage level (approximately $5\text{J}/\text{cm}^2$).

In the embodiments described, it is important to ensure
that there is not excess energy (and therefore heat)
25 build-up in the target, and therefore the inter pulse
duration is selected at a level to avoid this situation
occurring. It is preferred that the pulse repetition rate
is substantially in the range 3Hz maximum or less.

Claims:

- 5 1. Apparatus for cosmetic reduction of wrinkles on a
 superficial area of mammalian skin, the apparatus
 comprising a radiation delivery system for delivering
 a radiation beam of predetermined monochromatic
10 wavelength or narrow wavelength bandwidth to the
 skin, the radiation delivery system including a
 pulsation system for pulsing the radiation delivered
 according to a predetermined regime such that the
 total radiation energy density delivered to the skin
 is substantially in the range $0.5\text{J}/\text{cm}^2$ to $5\text{J}/\text{cm}^2$ per
 pulse.
- 15 2. Apparatus for cosmetic reduction of wrinkles on
 superficial mammalian skin, the apparatus comprising
 a radiation delivery system for delivering
 substantially monochromatic radiation, said radiation
20 being in a wavelength bandwidth of substantially 15nm
 or less and in at least one of the ranges 570nm to
 600nm and 750nm to 850nm , the delivery system
 including a pulsation system for pulsing the
 radiation delivered according to a predetermined
25 regime in which the radiation delivered to the skin
 has an energy density substantially in the range
 $0.5\text{J}/\text{cm}^2$ to $5\text{J}/\text{cm}^2$ per pulse.
- 30 3. Apparatus according to claim 1 or claim 2, wherein
 the radiation delivery system is set up to deliver
 substantially monochromatic radiation in a bandwidth

of substantially 15nm or less substantially in at least one of the ranges 577nm to 585nm and 800nm to 815nm.

- 5 4. Apparatus according to any preceding claim, wherein the radiation delivery system is set up to deliver radiation in a concentrated beam having a cross-section with a substantially uniform energy distribution across said beam cross section.
- 10 5. Apparatus according to any preceding claim, wherein the radiation delivery system is set up to deliver radiation in a concentrated beam having a diameter substantially in the range 1mm to 10mm.
- 15 6. Apparatus according to any preceding claim, wherein the pulsation system is set up to provide radiation pulses each pulse having a duration substantially in the range 10 μ s to 2ms.
- 20 7. Apparatus according to any preceding claim, wherein the pulsation system is set up to provide radiation pulses each pulse having a duration substantially in the range 200 μ s to 1ms.
- 25
-
8. Apparatus according to any preceding claim, wherein the radiation delivery system comprises a laser radiation delivery system.
- 30 9. Apparatus according to claim 8, wherein the laser radiation delivery system comprises a dye laser

radiation delivery system.

- 5 10. Apparatus according to claim 9, wherein the dye laser radiation delivery system comprises a flashlamp pumped dye laser including a pulse forming network arranged to pulse the laser according to the predetermined pulse regime.
- 10 11. Apparatus according to claim 8, wherein the laser radiation delivery system comprises a semiconductor laser radiation delivery system.
- 15 12. Apparatus according to any of claims 1 to 8, wherein the radiation delivery means includes a radiation emitting LED device.
- 20 13. Apparatus according to claim 12, wherein the radiation delivery means includes at least one radiation filter arranged to filter radiation to permit the substantially monochromatic radiation to be delivered to the skin.
- 25 14. Apparatus according to any preceding claim, further comprising a control system arranged to permit the energy density to be varied within the range $0.5\text{J}/\text{cm}^2$ and $5\text{J}/\text{cm}^2$.
-
- 30 15. Apparatus according to claim 14, wherein the control means is arranged to inhibit selection of an energy density substantially above $5\text{J}/\text{cm}^2$.

16. Apparatus according to any preceding claim, which includes an optical arrangement for focussing the radiation beam.

5 17. A method of cosmetically removing wrinkles from a superficial area of mammalian skin tissue having, in the order specified, an epidermal layer, a basal layer, and a dermal layer, which method comprises:
10 irradiating said dermal layer through said basal layer by means of visible or infra-red radiation, said irradiation being selected to be absorbed by a chromophore in said dermal layer such that collagen present in said dermal layer is heated, while said basal layer remains intact so as to substantially
15 inhibit contact of said dermal layer with ambient air, said irradiation having an energy density of substantially $5\text{J}/\text{cm}^2$ or less.

20 18. A method according to claim 17, wherein the irradiation is from a substantially monochromatic radiation source in a bandwidth of substantially 15nm or less.

25 19. A method according to claim 17, wherein said irradiation is from a coherent radiation source.

20. A method according to claim 17, wherein the source comprises a ruby laser arranged to target the dermis.

30 21. A method according to claim 17, wherein the source comprises a dye laser of wavelength selected to

target oxyhemoglobin present in blood vessels in said dermal layer.

- 5 22. A method according to claim 17, wherein the source comprises a dye laser, a ruby laser, or a semiconductor laser which scans said area of mammalian skin tissue.
- 10 23. A method according to claim 22, wherein the laser comprising said source is pulsed.
24. A method according to claim 23, wherein the pulsed laser has pulses of duration $10\mu\text{sec}$ to 2msec.
- 15 25. A method according to claim 17, in which said superficial area of mammalian skin tissue is treated with an artificial chromophore which is absorbed into the dermal layer.
- 20 26. A method according to claim 25, wherein the artificial chromophore is applied to the epidermal layer in the form of a liposome-containing topical formulation.
-

ABSTRACT

Wrinkle Reduction

5 Wrinkles are cosmetically removed from a superficial area
of mammalian skin tissue having an epidermal layer, a
basal layer, and a dermal layer, by irradiating the dermal
layer through the basal layer, the irradiation having an
energy density in the range $5\text{J}/\text{cm}^2$ or less, and being
10 selected to be absorbed by a chromophore in the dermal
layer such that collagen present in the dermal layer is
heated, while the basal layer remains intact so as to
substantially inhibit contact of the dermal layer with
ambient air.

15

FIG 1







FIG 2



is Page Blank (uspto)

FIG 3



This Page Blank (uspto)

FIG 5




FIG 6




FIG 7





FIG 8



PCT/6800/00749

3/4/00

VIDL

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

Page Blank (uspto)